

IN THE CLAIMS

1. (currently amended) A towing assembly, comprising:
a hitch ball receiver having at least one ~~cavity~~ acircular recess having a sidewall;
a hitch ball; and
a ~~member-connected~~ base integrally formed with the hitch ball, wherein the base is engageable with the sidewall of the recess to prevent rotation of the hitch ball during installation.
2. Cancelled
3. Cancelled.
4. (currently amended) The towing assembly of claim 3 ~~1~~, wherein said hitch ball receiver includes a first face and a second face, said recess being provided in said first face.
5. (original) The towing assembly of claim 4, further including a second recess, said second recess being provided in said second face.
6. (original) The towing assembly of claim 5, further including a spacer sized and shaped to be received in either of said recess and said second recess.
7. (previously presented) The towing assembly of claim 6, wherein said recess and said second recess having a substantially oval shape with two parallel flats thereon.
8. (currently amended) The towing assembly of claim 1, wherein said recess ~~cavity~~ is a channel.
9. (previously presented) The towing assembly of claim 8, wherein said hitch ball receiver is a ball mount head.
- 10 – 16 (cancelled)
17. (original) The towing assembly of claim 1, wherein said hitch ball receiver is a hitch bar.

18. (previously presented) The towing assembly of claim 17, wherein said hitch bar includes a tongue.

19. (currently amended) The towing assembly of claim 18 wherein said ~~ea~~vity recess is provided in said tongue.

20 – 21 (cancelled)

22. (currently amended) The towing assembly of claim 19, wherein said tongue includes a first face and a second face, said ~~ea~~vity recess being provided in said first face.

23. (previously presented) The towing assembly of claim 22, further including a second recess ~~ea~~vity, said second recess ~~ea~~vity being provided in said second face.

24. (currently amended) The towing assembly of claim 23, further including a spacer sized and shaped to be received in either of said ~~ea~~vity recess or ~~and~~ said second recess ~~ea~~vity.

25. (currently amended) The towing assembly of claim 24, wherein said recess ~~ea~~vity and said second recess ~~ea~~vity have a substantially oval shape with two parallel flats thereon.

26. – 33 (cancelled)

34. (cancelled)

35. (cancelled)